

# ANGUS

## VESSEL PARTICULARS



<b>TYPE</b>	Multi Purpose / Heavy Lift Vessel
<b>BUILDER</b>	Tongfang Jiangxin Shipbuilding Co.
<b>BUILT</b>	2011
<b>FLAG</b>	Marshall Island
<b>HOMEPORT</b>	Majuro
<b>CLASS</b>	Lloyd's Register
<b>IMO NO</b>	9469780
<b>CALL SIGN</b>	V7A4273

### TONNAGE AND CAPACITY

<b>DWAT</b>	19.617
<b>GT / NT</b>	13.816 / 5.359
<b>GRAIN / BALE</b>	20.003 cbm / 19.903 cbm
<b>TEU CAPACITY</b>	524 TEU on deck, 440 TEU in hold

### DIMENSIONS

<b>LOA / LBP</b>	148,00 m / 140,30 m
<b>BREADTH</b>	23,40 m
<b>DRAFT</b>	max. 9,81 m

### CRANES

<b>TYPE</b>	LIEBHERR Slectro Hydraulic port-side mounted
<b>CAPACITY</b>	2 x 240 mts, combinable up to 480 mts
<b>OUTREACH</b>	5,0 to 36,5 m

### MAIN ENGINE

<b>TYPE</b>	WÄRTSILÄ 6RTA 48T-BC
<b>MCR</b>	8.730 kw

### SPEED / CONSUMPTION

<b>LADEN</b>	16,0 kts on abt. 37,0 mts HFO
<b>BALLAST</b>	16,0 kts on abt. 30,0 mts HFO

### ADDITIONAL FEATURES

A60 Bulkhead  
Equipped for carriage of IMO cargo  
Mechanical hold ventilation  
AMSA fitted

### CARGO HOLDS AND HATCHES

<b>HOLD NO 1</b>	6,3 m x 12,84 m x 13,35 m
<b>TANK TOP</b>	abt. 80,9 sqm
<b>TWENDECK</b>	n/a
<b>HATCH COVER</b>	abt. 93,1 sqm
<b>TOTAL</b>	abt. 174 sqm

<b>HOLD NO 2</b>	25,90 m x 18,50 m x 13,35 m
<b>TANK TOP</b>	abt. 466,2 sqm
<b>TWENDECK</b>	abt. 466,2 sqm
<b>HATCH COVER</b>	abt. 466,2 sqm
<b>TOTAL</b>	abt. 1.429 sqm

<b>HOLD NO 3</b>	52,25 m x 18,50 m x 13,35 m
<b>TANK TOP</b>	abt. 945 sqm
<b>TWENDECK</b>	abt. 945 sqm
<b>HATCH COVER</b>	abt. 984 sqm
<b>TOTAL</b>	abt. 2.874 sqm

### DECK STRENGTH

<b>TANK TOP</b>	20,0 mt / sqm
<b>TWENDECK</b>	4,0 mt / sqm
<b>HATCH COVER</b>	2 mt / sqm

### FEATURES

<b>HATCH COVERS</b>	steel folding
<b>TWENDECKS</b>	multilevel, can be used as bulkheads



**AUERBACH**  
Schiffahrt

# MALCOLM

## VESSEL PARTICULARS



<b>TYPE</b>	Multi Purpose / Heavy Lift Vessel
<b>BUILDER</b>	Tongfang Jiangxin Shipbuilding Co.
<b>BUILT</b>	2011
<b>FLAG</b>	Marshall Island
<b>HOMEPORT</b>	Majuro
<b>CLASS</b>	Lloyd's Register
<b>IMO NO</b>	9469778
<b>CALL SIGN</b>	V7A4274

### TONNAGE AND CAPACITY

<b>DWAT</b>	19.617
<b>GT / NT</b>	13.816 / 5.359
<b>GRAIN / BALE</b>	20.003 cbm / 19.903 cbm
<b>TEU CAPACITY</b>	524 TEU on deck, 440 TEU in hold

### DIMENSIONS

<b>LOA / LBP</b>	148,00 m / 140,30 m
<b>BREADTH</b>	23,40 m
<b>DRAFT</b>	max. 9,81 m

### CRANES

<b>TYPE</b>	LIEBHERR Slectro Hydraulic port-side mounted
<b>CAPACITY</b>	2 x 240 mts, combinable up to 480 mts
<b>OUTREACH</b>	5,0 to 36,5 m

### MAIN ENGINE

<b>TYPE</b>	WÄRTSILÄ 6RTA 48T-BC
<b>MCR</b>	8.730 kw

### SPEED / CONSUMPTION

<b>LADEN</b>	16,0 kts on abt. 37,0 mts HFO
<b>BALLAST</b>	16,0 kts on abt. 30,0 mts HFO

### ADDITIONAL FEATURES

A60 Bulkhead  
Equipped for carriage of IMO cargo  
Mechanical hold ventilation  
AMSA fitted

### CARGO HOLDS AND HATCHES

<b>HOLD NO 1</b>	6,3 m x 12,84 m x 13,35 m
<b>TANK TOP</b>	abt. 80,9 sqm
<b>TWENDECK</b>	n/a
<b>HATCH COVER</b>	abt. 93,1 sqm
<b>TOTAL</b>	abt. 174 sqm

<b>HOLD NO 2</b>	25,90 m x 18,50 m x 13,35 m
<b>TANK TOP</b>	abt. 466,2 sqm
<b>TWENDECK</b>	abt. 466,2 sqm
<b>HATCH COVER</b>	abt. 466,2 sqm
<b>TOTAL</b>	abt. 1.429 sqm

<b>HOLD NO 3</b>	52,25 m x 18,50 m x 13,35 m
<b>TANK TOP</b>	abt. 945 sqm
<b>TWENDECK</b>	abt. 945 sqm
<b>HATCH COVER</b>	abt. 984 sqm
<b>TOTAL</b>	abt. 2.874 sqm

### DECK STRENGTH

<b>TANK TOP</b>	20,0 mt / sqm
<b>TWENDECK</b>	4,0 mt / sqm
<b>HATCH COVER</b>	2 mt / sqm

### FEATURES

<b>HATCH COVERS</b>	steel folding
<b>TWENDECKS</b>	multilevel, can be used as bulkheads